

AGGREGATE

Los Angeles Abrasion Machine



The Los Angeles Abrasion Machine is used for determination of the aggregates resistance to fragmentation. The machine consists of an electronic control unit and a steel drum having an internal diameter of 711 mm and internal length of 508 mm. The drum is rotated at a speed of 31-33 r.p.m. The internal shelf provided with the machine conforms to ASTM, AASHTO and EN standards. The machine is equipped with an automatic counter, when the preset revolution count is reached, the machine will stop automatically. The drum is equipped with an interlock device which allows the operator to lock the drum into position for easy loading/unloading of the sample. A steel tray is supplied with the machine for easy discharge of specimen and abrasive charges.

The standard model can be supplied with a safety/noise reduction cabinet. The cabinet is lined internally with soundproofing material to reduce sound level conforming to CE directives. The cabinet must be ordered with the Los Angeles machine if required, as the electronic control unit will be installed on the safety cabinet at the time of manufacture. The cabinet is equipped with an electric safety device which automatically stops the rotation of the drum when the door is opened, conforming to CE directives.

Product Gallery



You May Also Be Interested In



Large Capacity Sample Splitter

PAG-412



Sand Equivalent Shaker

PAG-402



**Aggregate Impact Value (AIV)
Test Machine**

PAG-413

Review Product on Our Website

To access up-to-date technical details, images, and documentation for this product, you can scan the QR code on the right using your smartphone camera or visit our website directly.

