


SOIL

Automatic CBR Test Machine



The Automatic CBR (California Bearing Ratio) Test Machine is designed for the laboratory determination of the CBR value of highway sub-base and subgrade materials, as well as for evaluating the strength of cohesive soils with a maximum particle size of 19 mm (3/4").

The machine consists of a robust, compact two-column load frame with an adjustable upper crosshead, driven by a precision electromechanical ram with a maximum capacity of 50 kN. It is equipped with an advanced data acquisition and processing system for accurate measurement and real-time display of load and penetration values.

The system applies load to the penetration piston at a constant, controlled rate, enabling precise measurement of applied force and piston penetration at predefined intervals. This design ensures full compliance with BS, EN, ASTM, and AASHTO standards, allowing multiple test standards to be performed on the same machine without modification.

For ease of operation, rapid platen positioning is provided via front-panel up/down control buttons, allowing quick and safe adjustment to the test position.

The Automatic CBR Test Machine is supplied complete with:

50 kN high-accuracy load cell

Standard penetration piston

Linear potentiometric displacement transducer (25 mm travel, 0.001 mm resolution)

This configuration ensures high precision, repeatability, and reliability for routine quality control and research applications in geotechnical and pavement engineering laboratories.

Related Standards

EN 13286-47; BS 1377:4; ASTM D1883; AASHTO T193; NF P94-078; AS 1289.6.1.1; UNI CNR 10009

You May Also Be Interested In



Plastic Limit Test Set

PSO-217



**Liquid Limit Casagrande,
Manual**

PSO-218.1



Sand Cone Test Set

PSO-214

Review Product on Our Website

To access up-to-date technical details, images, and documentation for this product, you can scan the QR code on the right using your smartphone camera or visit our website directly.

